

AD-A141 488

A NOTE ON LOSSLESS DATABASE DECOMPOSITIONS(U) STANFORD
UNIV CA DEPT OF COMPUTER SCIENCE M Y VARDI 21 DEC 83
AFOSR-TR-84-0358 AFOSR-80-0212

1/1


UNCLASSIFIED

F/G 9/2

NL



END
DATE
FILMED
7-84
DTIC



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

DTIC
SELECTE

MAY 24 1984

1. REPORT SECURITY CLASSIFICATION

UNCLASSIFIED

2. SECURITY CLASSIFICATION AUTHORITY

3. DECLASSIFICATION/DOWNGRADING SCHEDULE

1b. RESTRICTIVE MARKINGS

3. DISTRIBUTION/AVAILABILITY OF REPORT

Approved for public release; distribution unlimited.

4. PERFORMING ORGANIZATION REPORT NUMBER(S)

RJ 4145 (45933) 12/21/83

IBM Research Laboratory, San Jose CA 95193

5. MONITORING ORGANIZATION REPORT NUMBER(S)

AFOSR-TR. 84-0358

6. NAME OF PERFORMING ORGANIZATION

Stanford University

7b. OFFICE SYMBOL

(If applicable)

7a. NAME OF MONITORING ORGANIZATION

Air Force Office of Scientific Research

8. ADDRESS (City, State and ZIP Code)

Computer Science Department
Stanford CA 94305

7b. ADDRESS (City, State and ZIP Code)

Directorate of Mathematical & Information
Sciences, Bolling AFB DC 203329. NAME OF FUNDING/SPONSORING
ORGANIZATION

AFOSR

10b. OFFICE SYMBOL

(If applicable)

NM

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

AFOSR-80-0212

10c. ADDRESS (City, State and ZIP Code)

Bolling AFB DC 20332

10. SOURCE OF FUNDING NOS.

PROGRAM
ELEMENT NO.

61102F

PROJECT
NO.

2804

TASK
NO.

A2

WORK UNIT
NO.

11. TITLE (Include Security Classification)

A NOTE ON LOSSLESS DATABASE DECOMPOSITIONS

12. PERSONAL AUTHOR(S)

Moshe Y. Vardi*

13a. TYPE OF REPORT

Technical

13b. TIME COVERED

FROM TO

14. DATE OF REPORT (Yr., Mo., Day)

21 DEC 83

15. PAGE COUNT

8

16. SUPPLEMENTARY NOTATION

*IBM Research Laboratory, San Jose CA 95193.

17. COSATI CODES

FIELD

GROUP

SUB. GR.

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

pp-1-a

83

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

It is known that under a wide variety of assumptions a database decomposition is lossless if and only if the database scheme has a lossless join. Biskup, Dayal, and Bernstein have shown that when the given dependencies are functional then the database scheme has a lossless join if and only if one of the relation scheme is a key for the universal scheme. In this note the investigators supply an alternative proof of that characterization. The proof uses tools from the theory of embedded join dependencies and the theory of tuple and equality generating dependencies, but is, nevertheless, much simpler than the previously published proof.

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT

UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT. ☐ DTIC USERS ☐

21. ABSTRACT SECURITY CLASSIFICATION

UNCLASSIFIED

22a. NAME OF RESPONSIBLE INDIVIDUAL

Dr. Robert N. Buchal

22b. TELEPHONE NUMBER

(Include Area Code)

(202) 767- 4939

22c. OFFICE SYMBOL

NM

AD-A141 488

DTIC FILE COPY

RJ 4145 (45933) 12/21/83
Computer Science

Research Report

AFOSR-TR- 84 - 0358

A NOTE ON LOSSLESS DATABASE DECOMPOSITIONS

Moshe Y. Vardi

IBM Research Laboratory
San Jose, California 95193

SEARCHED
SERIALIZED
INDEXED
FILED



A1

LIMITED DISTRIBUTION NOTICE

This report has been submitted for publication outside of IBM and will probably be copyrighted if accepted for publication. It has been issued as a Research Report for early dissemination of its contents. In view of the transfer of copyright to the outside publisher, its distribution outside of IBM prior to publication should be limited to peer communications and specific requests. After outside publication, requests should be filled only by reprints or legally obtained copies of the article (e.g., payment of royalties).

IBM

Research Division
Yorktown Heights, New York • San Jose, California • Zurich, Switzerland

84 05 15 320

RJ 4145 (45933) 12/21/83
Computer Science

A NOTE ON LOSSLESS DATABASE DECOMPOSITIONS

Moshe Y. Vardi

IBM Research Laboratory
San Jose, California 95193

ABSTRACT: It is known that under a wide variety of assumptions a database decomposition is lossless if and only if the database scheme has a lossless join. Biskup, Dayal, and Bernstein have shown that when the given dependencies are functional then the database scheme has a lossless join if and only if one of the relation scheme is a key for the universal scheme. In this note we supply an alternative proof of that characterization. The proof uses tools from the theory of embedded join dependencies and the theory of tuple and equality generating dependencies, but is, nevertheless, much simpler than the previously published proof.

1. Introduction

A significant portion of research on relational database theory has been concerned with the properties of *decompositions*. The generic problem can be described as follows. Given a "universal" relation scheme presented as a set of attributes and a set of dependencies, what are the conditions under which it can be decomposed into a collection of relation schemes, each with its own sets of attributes and dependencies, having some desired properties. The properties considered were, at first, various *normal forms*. (see [Ma, Ul]).

A basic assumption underlying these ideas is that when a universal scheme is decomposed into smaller schemes, each of the universal relations associated with it is decomposed into smaller relations using the *projection* operation, i.e., each such relation is projected onto each one of the smaller schemes. For a decomposition to be useful, it should be *lossless*. In other words, it should be possible to reconstruct the universal relations from their projections. The desirability of this property is called in [BBG] the *representation principle*.

The property of losslessness has been studied in numerous papers [BR,MMSU,MUV,Va]. It has been shown there that, under a wide variety of assumptions, a decomposition is lossless if and only if the database scheme has a lossless join. When the given dependencies are functional the following characterization of database schemes that have lossless join is given in [BDB]: *a database scheme has a lossless join if and only if one of the relation schemes is a key of the universal scheme.*

The proof of the above characterization in [BDB] is quite involved and consists of a detailed study of the test for losslessness in [ABU]. In this note we describe an alternative proof for that characterization. The proof uses more advanced tools from dependency theory, but is, we believe, much simpler. Specifically, we use the theory of *embedded join dependencies* [BV1] and the theory of *tuple and equality generating dependencies* [BV2,BV3]. Our intention is to demonstrate how "higher-level" notions from dependency theory can be used to study its most fundamental questions. We believe that techniques used here could also be applicable to

other problems.

2. The Theorem

We assume familiarity with the terminology and concepts of relational database theory as presented in [Ma, Ul]. The *universe* U is a finite set of *attributes*. All attribute sets are subsets of U . An *attribute set collection* (asc) is a set $R = \{R_1, \dots, R_k\}$ of distinct attribute sets. We denote attribute sets by lightface letters and asc's by boldface letters. A *database scheme* is an asc $R = \{R_1, \dots, R_k\}$ such that $\bigcup_{i=1}^k R_i = U$. A relation is a relation on U unless explicitly specified otherwise. We use $I[X]$ to denote the *projection* of the relation I on the attribute set X , and $\ast I_j$ to denote the *join* of the set $\{I_j\}$ of relations. We assume that the relations we are dealing with and, accordingly, the dependencies that refer to them are *typed*, that is, distinct attributes have disjoint domains. We also assume that all relations are finite.

A *functional dependency* (fd) is a statement $X \rightarrow Y$, where X and Y are attribute sets. It is satisfied by a relation I if for all tuples s and t in I , if $s[X] = t[X]$ then $s[Y] = t[Y]$. A *total join dependency* (tjd) is a statement $\ast[R]$, where R is a database scheme $\{R_1, \dots, R_k\}$. It is satisfied by a relation I if $I = \ast_{i=1}^k I[R_i]$.

Let Σ be a set of dependencies and let τ be a dependency. We say that Σ implies τ , denoted $\Sigma \models \tau$ if every relation on U that satisfies all dependencies in Σ satisfies also τ . A database scheme R has a *lossless join* with respect to Σ if $\Sigma \models \ast[R]$. A set Σ of fd's is *embeddable* in a database scheme R if for each fd $X \rightarrow Y$ in Σ there is some R in R such that $XY \subseteq R$.¹

Theorem. [BDB] Let Σ be a set of fd's and let R be a database scheme.

- (1) If R has a lossless join with respect to Σ , then there is some $R \in R$ such that $\Sigma \models R \rightarrow U$.

¹ Following convention we denote set union by juxtaposition.

- (2) If Σ is embeddable in R and there is some $R \in \mathcal{R}$ such that $\Sigma \models R \rightarrow U$, then R has a loss-less join with respect to Σ . ■

3. The Necessary Condition

3.1. Preliminary Definitions

We prove the necessary condition via an excursion through the theory of tuple and equality generating dependencies. We need first to review some definitions.

A *valuation* is a mapping on the domain of which tuples and relations are constructed. We can extend the definition of a valuation to tuples, in a component-wise manner, and to relations, in a tuple-wise manner.

Equality generating dependencies generalize fd's. An equality generating dependency (egd) says that if some tuples, fulfilling certain equalities, exist in the database, then some values in these tuples must be equal. Formally, an egd is a pair $\langle (a_1, a_2), I \rangle$, where I is a relation and a_1 and a_2 occur in I . A relation J satisfies $\langle (a_1, a_2), I \rangle$ if for any valuation h such that $h(I) \in J$ we have $h(a_1) = h(a_2)$. Note that if $a_1 = a_2$ then $\langle (a_1, a_2), I \rangle$ is trivially satisfied by every relation.

Lemma 1. [BV3] Let h be a valuation and let $\langle (a_1, a_2), I \rangle$ be an egd. Then $\langle (a_1, a_2), I \rangle \models \langle (h(a_1), h(a_2)), h(I) \rangle$. ■

Total tuple generating dependencies generalize tjd's. A total tuple generating dependency (ttgd) says that if some tuples, fulfilling certain equalities, exist in the database, then another tuple, whose values are taken from these tuples, must also exist in the database. Formally, a ttgd is a pair $\langle w, I \rangle$, where I is a relation and w is a tuple whose entries occur in I . A relation J satisfies $\langle w, I \rangle$ if for any valuation h such that $h(I) \subseteq J$, we have that $h(w) \in J$. Note that if $w \in I$, then $\langle w, I \rangle$ is trivially satisfied by every relation.

Fd's and tjd's can be viewed as a special case of egd's and ttgd's, respectively. Consider the fd $X \rightarrow A$, where $A \in X$. We define an egd $\tau_{X \rightarrow A} = \langle (a0, a1), J \rangle$ as follows: J consists of

two tuples u and v such that $u[X] = v[X]$, $u[B] \neq v[B]$ for all $B \in X$, $u[A] = a0$, and $v[A] = a1$. We leave it to the reader to verify that a relation K satisfies $X \rightarrow A$ if and only if it satisfies $\tau_{X \rightarrow A}$. Consider the tjd $*[R]$, where $R = \{R_1, \dots, R_k\}$. We define a ttgd $\tau_R = \langle w, I \rangle$, where w is an arbitrary tuple, $I = \{w_1, \dots, w_k\}$, $w_i[R_i] = w[R_i]$, and if $A \in R_i$ then $w_i[A]$ has a unique occurrence in I . It is shown in [ASU] that a relation K satisfies $*[R]$ if and only if it satisfies τ_R .

Example 1. Let $U = ABCD$. Let I and J be the relations:

	A	B	C	D		A	B	C	D
I:	a0	b0	c1	d0	J:	a0	b0	c0	d0
	a0	b1	c0	d1		a1	b0	c0	d1

Let u be the tuple:

A	B	C	D
a0	b0	c0	d0

Let τ_1 be the ttgd $\langle u, I \rangle$. Then τ_1 is equivalent to the tjd $*[ABD, AC]$. Let τ_2 be the egd $\langle (a0, a1), J \rangle$. Then τ_2 is equivalent to the fd $BC \rightarrow A$. ■

An algorithm for testing implication of egd's and ttgd's, called the *chase*, was presented in [BV2], following earlier algorithms for testing implications of fd's and tjd's [ABU, MMS]. We present here the special case where the implying dependencies are functional. Without loss of generality we assume that the given fd's have a single attribute on their right-hand side. A *chase* of a relation I by a set Σ of fd's is a maximal sequence of distinct relations I_0, I_1, \dots such that $I = I_0$ and I_{n+1} is obtained from I_n by an application of a *chase rule*. To each fd in Σ there corresponds a chase rule;

FD-rule (for an fd $X \rightarrow Y$ in Σ): I_{n+1} is obtained from I_n by identifying all occurrences of $u[A]$ with all occurrences of $v[A]$, for some tuples u and v in I_n such that $u[X] \neq v[X]$.

To make the FD-rule unambiguous, we assume that the domain of values for each attribute is totally ordered and whenever two values are identified, the greater is identified with the smaller. Given $\langle w, I \rangle$, we take $w(A)$ as the smallest value in the domain for A . (We can

always rename the values in w and I so that this is true). Similarly, given $\langle (a_1, a_2), I \rangle$, we take a_1 as the smallest values in the domain for A and a_2 as the next smallest. Thus, the values in w or a_1 do not change in the chase and a_2 can be identified only with a_1 . It is shown in [BV2] that all chases of I by Σ are finite and they have the same final relation, denoted $\text{chase}_\Sigma(I)$.

To trace the tuples of I in the chase we adjoin to each tuple an ordinal number, that is $I = \{w_1, \dots, w_k\}$. The ordinal numbers do not change during the computation of the chase, though the values in the tuples may change by the FD-rules. Thus, I_n consists of the tuples w_1^n, \dots, w_k^n (not necessarily distinct), which correspond to the tuples w_1, \dots, w_k of I . We denote by w'_i the tuple in $\text{chase}_\Sigma(I)$ that correspond to w_i .

Lemma 2. [BV2] Let Σ be a set of fd's and let $I = \{w_1, \dots, w_k\}$ be a relation.

- (1) $\Sigma \models \langle w, I \rangle$ if and only if $w \in \text{chase}_\Sigma(I)$.
- (2) $\Sigma \models \langle (w_i[A], w_j[A]), I \rangle$ if and only if $w'_i[A] = w'_j[A]$. ■

3.2. The Proof

Suppose that $R = \{R_1, \dots, R_k\}$ has a lossless join with respect to a set Σ of fd's. That is, $\Sigma \models^* [R]$. If $U \in R$, then the claim of the theorem is trivially satisfied. So assume that $U \notin R$. Let $\tau_R = \langle w, I \rangle$. That is, $I = \{w_1, \dots, w_k\}$, $w_i[R_i] = w[R_i]$, and if $A \in R_i$ then $w_i[A]$ has a unique occurrence in I . Since $\Sigma \models^* [R]$, also $\Sigma \models \tau_R$. By Lemma 2, there is some i such that $w'_i = w$. That is, $w'_i[A] = w[A]$ for all $A \in R_i$. By Lemma 2 we have that $\Sigma \models \langle (w_i[A], w[A]), I \rangle$, for all $A \in R_i$. Let $\tau_{R_i \rightarrow A} = \langle (a0, a1), J \rangle$. That is, J consists of two tuples u and v such that $u[R_i] = v[R_i]$, $u[B] \neq v[B]$ for all $B \in R_i$, $u[A] = a0$, and $v[B] = a1$. We define a valuation h such that $h(w_i) = u$ and $h(w_j) = v$ for $j \neq i$. It is easy to see that h is well defined, $h(I) = J$, $h(w_i[A]) = a0$ and $h(w[A]) = a1$. By Lemma 1, $\langle (w_i[A], w[A]), I \rangle \models \tau_{R_i \rightarrow A}$. It follows that $\Sigma \models R_i \rightarrow A$ for all $A \in R_i$, and, consequently, $\Sigma \models R_i \rightarrow U$.

4. The Sufficient Condition

4.1. Preliminary Notions

We prove the sufficient condition via an excursion through the theory of join dependencies. We need first to review some definitions.

For an asc $R = \{R_1, \dots, R_k\}$, the attribute set of R , denoted $attr(R)$, is $\bigcup_{i=1}^k R_i$. A *join dependency* (jd) is a statement $*[R]$, where R is an asc $\{R_1, \dots, R_k\}$. (We also use the notation $*[R_1, \dots, R_k]$.) It is satisfied by a relation I if $I[attr(R)] = \bigcap_{i=1}^k I[R_i]$. Note that a *tjd* is a special case of a jd. Jd's are called in [MMS] *embedded* jd's. Let R and S be asc's such that $attr(R) = attr(S)$. We say that S *covers* R , denoted $R \leq S$, if for all $R \in \mathcal{R}$ there is some $S \in \mathcal{S}$ such that $R \subseteq S$.

Lemma 3. [BV1] Let X , Y , and Z be attribute sets, and let R and S be asc's. Then

- (1) $\emptyset \models *[X]$.
- (2) If $R \leq S$, then $*[R] \models *[S]$.
- (3) If $attr(S) \in \mathcal{R}$, then $\{*[R], *[S]\} \models *[R - \{attr(S)\} \cup S]$.
- (4) $X \rightarrow Y \models *[XY, XZ]$. ■

4.2. The Proof

It is shown in [BB] that if $\Sigma \models R \rightarrow U$, then there is a sequence $X_1 \rightarrow Y_1, \dots, X_n \rightarrow Y_n$ of fd's from Σ with the following property: Let $R_0 = R$ and $R_i = R_{i-1} Y_i$, $1 \leq i \leq n$. Then $X_i \subseteq R_{i-1}$, for $1 \leq i \leq n$, and $R_n = U$. We show by induction on i that $\Sigma \models *[R, X_1 Y_1, \dots, X_i Y_i]$.

Basis ($i=0$). By (1) of Lemma 3, we have $\Sigma \models *[R]$.

Induction. Suppose that $\Sigma \models *[R, X_1 Y_1, \dots, X_{i-1} Y_{i-1}]$. Since $X_i \subseteq R_{i-1}$, we have that $X_i \rightarrow Y_i \models *[X_i Y_i, R_{i-1}]$ by (4) of Lemma 3. Since $R \cup (\bigcup_{j=1}^{i-1} X_j Y_j) = R_{i-1}$,

$\Sigma \models^* [R, X_1 Y_1, \dots, X_i Y_i]$ by (3) of Lemma 4.

In particular we have $\Sigma \models^* [R, X_1 Y_1, \dots, X_n Y_n]$. But by assumption $R \in R$ and Σ is embeddable in R , so $\{R, X_1 Y_1, \dots, X_n Y_n\} \leq R$. It follows that $\Sigma \models^* [R]$ by (2) of Lemma 4.

References

- [ABU] Aho, A.V., Beeri, C., Ullman, J.D.: The theory of joins in relational databases. *ACM Trans. on Database Systems* 4(1979), pp.297-314.
- [BB] Beeri, C., Bernstein P.A.: Computational problems related to the design of normal form relational schemas. *ACM Trans. on Database Systems* 4(1979), pp. 30-59.
- [BBC] Beeri, C., Bernstein, P.A., Goodman, N.: A sophisticates' introduction to database normalization theory. *Proc. Int'l Conf. on Very Large Databases*, Berlin, 1978, pp. 113-124.
- [BDB] Biskup, J., Dayal, U., Bernstein, P.A.: Synthesizing independent database schemas. *Proc. ACM Int'l Conf. on Management of Data*, Boston, 1979, pp. 143-151.
- [BR] Beeri, C., Rissanen, J.: Faithful representation of relational database schemes. *IBM Research Report*, San Jose, 1980.
- [BV1] Beeri, C., Vardi, M.Y.: On the properties of join dependencies. In *Advances in Database Theory* (H. Gallaire, J. Minker and J.M. Nicolas, eds.), Plenum, 1981, pp. 25-72.
- [BV2] Beeri, C., Vardi, M.Y.: A proof procedure for data dependencies. *Dept. of Computer Science, The Hebrew University of Jerusalem*, Dec. 1980.
- [BV3] Beeri, C., Vardi, M.Y.: Formal system for tuple and equality generating dependencies. *Dept. of Computer Science, The Hebrew University of Jerusalem*, April 1981. To appear in *SIAM J. Computing*.
- [Ma] Maier, D., *The Theory of Relational Databases*, Computer Science Press, Rockville, Maryland, 1983.

- [MMS] Maier, D., Mendelzon, A.O., Sagiv, Y.: Testing Implications of data dependencies. ACM Trans. on Database Systems 4(1979), pp. 455-469.
- [MMSU] Maier, D., Mendelzon, A.O., Sadri, F., Ullman, J.D.: Adequacy of decompositions of relational databases. In *Advances in Database Theory* (H. Gallaire, J. Minker, and J.M. Nicolas, eds.), Plenum Press, 1981, pp. 101-114.
- [MUV] Maier, D., Ullman, J.D., Vardi, M.Y.: The revenge of the jd. Proc. ACM Symp. on Principles of Database Systems, Atlanta, March 1982, pp. 279-287.
- [R1] Rissanen, J.: Independent components of relations. ACM Trans. on Database Systems 2(1977), pp. 317-325.
- [UI] Ullman, J. D., Principles of Database Systems, Computer Science Press, Rockville, Maryland, 1983.
- [Va] Vardi, M.Y.: On the decomposition of relational databases. Proc. 23rd IEEE Symp. on Foundation of Computer Science, Chicago, Nov. 1982, pp. 176-187.

DATE
FILMED
— 8